Direct Drive Fan
Single & Double Shaft 5.0" Diameter, Open Air Over

APPLICATIONS:

To meet manufacturer's requirements for direct drive fans and blowers.

FEATURES:

- Bearings Have All Angle Thrust System
- Continuous Duty, Air Over
- 24" Line Leads Unless Otherwise Noted
- Automatic Reset Thermal Overload Protector
- Connection Information Furnished in the Nameplate Data
- Shaded Pole Design Except Where Noted




Figure A




Figure B

5.0" Diameter, Stud or Hub Ring Mount (2.5") (Figure A)

HP	RPM/ Spds.	Voltage	Catalog Number	List	Bearings	NEMA®† Frame	Amps	Shaft N	Base XD	Shell XI	Total C	Stud YM	Ship Wt. (lbs)
1/15	1050	115	1334	$134	SAB	42Y	2.8	1.9	--	3.3	5.2	0.6	10
	1050	115	1335	$136	SAB	42Y	2.8	1.3	3.8	3.3	5.7	--	12
	1050	115	1342	$126	SAB	42Y	2.6	2.8	--	3.8	6.6	0.6	10
	1050/2	115	1333	$138	SAB	42Y	3	1.9	--	3.3	5.2	0.6	11
1/10	1050	115	1336	$124	SAB	42Y	3.7	1.8	--	3.8	5.7	0.6	11
1/8	1050	115	1337	$129	SAB	42Y	5.5	5.0	5.0	4.5	10.4	0.9	13
1/6	1050	115	1127P	$101	SAB	42Y	3.0	4.0	5.0	4.3	9.4	--	12
	1050	115	2166P	$198	SAB	42Y	5.2	3.5	4.5	3.8	8.9	--	10
1/5	1050	115	1340	$133	SAB	42Y	7.1	2.2	5.2	4.7	7.9	0.9	14
	1050/3	115	1338P	$151	SAB	42Y	3.2	4.9	5.5	5.0	10.9	0.9	14
	1050/3	208-230	1339	$164	SAB	42Y	3.9	4.9	5.5	5.0	10.9	0.9	14
1/4	1050	115	1341	$134	SAB	42Y	8.9	2.6	5.7	5.2	8.7	0.9	15

5.0" Diameter, Resilient Base, Double Shaft (Figure B)

HP	RPM/ Spds.	Voltage	Catalog Number	List	Bearings	Rotation LE	Amps	Shaft N	Shaft XN	Shell XI	Total C	Ship Wt. (lbs)
1/10	1050/2	115	2819	$123	SAB	CCW	3.7	4.0	4.0	3.8	14.3	10
	1050/2	230	2820	$244	SAB	CCW	2.0	4.0	4.0	3.3	14.3	10
	1050/4	115	2818	$196	SAB	CCW	4.8	8.4	8.4	4.6	22.4	11
	1050/5	115	2827P	$265	SAB	CW	2.5	10.0	10.0	4.1	25.2	9
	1550/3	115	2817	$273	SAB	CCW	3.8	8.4	8.4	4.6	22.4	8
1/6	1625/2	115	1238	$176	SAB	CCW	2.3	7.0	7.0	3.9	18.9	11
1/5	1075	208-230	1124	$209	SAB	CW	1.3	5.7	5.7	4.1	16.5	12
1/4	1550/3	230	1221P	$262	SAB	CCW	1.6	8.0	8.0	4.3	20.9	14