Permanent Split Capacitor Packaged Terminal A/C – Heat Pump Open, Air Over

APPLICATIONS:


Designed to meet manufacturer's requirements for use in package terminal air conditioners or heat pump units.


FEATURES:

- Bearings Have All Angle Thrust System
- Designed for use with 370V Capacitors
- Continuous Duty, Air Over
- Automatic Reset Thermal Overload Protector

A 

B 

C 

D 

Single Shaft, Direct Drive Blower - 5.0" Diameter

HP	RPM / Spds.	Voltage	Catalog Number	Cap MFD	Amps	Shaft Length	Total Length	Mount	Fig.	Rotation	Ship Wt.
1/15	1040/3	115	1377	7.5	1.3	6.5	10.6	Flex	C	CCWLE	
1/30	1100/3	115	1374	5.0	0.50	8.5	13.6	Resilient	D	CWLE	9
	1100/3	115-127	4125	4.0	0.53	8.0	13.2	Resilient	D	CCWLE	12
	1600/3	115-127	1269	3.0	0.51	6.5	11.4	Resilient	D	CCWLE	7
	1100/3	115	1218	7.5	0.73	7.0	10.8	Flex	C	CCWLE	7
	1100/3	277	1259	3.0	0.32	7.0	10.8	Flex	C	CCWLE	5
1/20	1100/3	115	1258	7.5	1.10	7.0	10.8	Flex	C	CCWLE	10
	1100/3	115	1676	5.0	0.55	8.9	13.1	Resilient	D	CWLE	12
	1075/3	208-230	1378	5.0	0.55	6.5	10.6	Flex	C	CCWLE	12
	1075/3	277	4137	4.0	0.55	6.5	9.9	3 Lugs	A	CCWLE	9
	1100/3	277	1264	3.0	0.42	7.0	10.8	Flex	C	CCWLE	7
1/16	850/3	277	1678	4.0	0.50	2.3	6.3	3 Lugs	B	CWLE	12
1/15	1075/3	265	1365	4.0	0.60	7.0	10.8	Flex	C	CCWLE	8
1/12	1375/3	115-127	1211	6.0/7.5	1.35	6.5	11.4	Resilient	D	CCWLE	7
1/5	925/3	208-240	4129	6.0	1.90	7.0	11.6	Flex	C	CCWLE	8
1/4	970/3	115	4130	12.5	6.00	7.0	11.8	Flex	C	CCWLE	8
	1050/3	277	1962	7.5	1.60	7.0	12.6	Flex	C	CCWLE	8

Catalog Number	OEM Number	Industry Number	Catalog Number	OEM Number	Industry Number
1211	70556336	------	1678	X70500269-01/MOT2852	5KSP29DK1507S
1218	705563-01	------	1961	705563-09	SKCP29DK6018S
1258	705563-02		1962	700215-48	5KCP29MK6109S
1259	70556307	5KCP29BK6016AS	4125	700216-92	5KCP29BK5875S
1264	70556308	5KCP29FK6017S	4129	700215-42	SKCP29KK4878AS
1269	70556329	------	4130	700215-21	SKCP29MK6102S
1374	7/MOT1878	5KSP29DK1507S	4136	705563-14	5KCP29FK6023S
1676	X70500149-02	5KSP29DK1507S	4137	700215-45	SKCP29FK9775