Refrigeration Condenser Fan 5.0" and 5.6" Diameter
Open Drip-Proof, Totally Enclosed, Air Over and Open Air Over

APPLICATIONS:

Condenser cooling fan motors to meet manufacturer's requirements for commercial refrigeration units.

FEATURES:

- OEM Direct Replacements
- Single Speed
- Automatic Reset Thermal Overload Protector
- Designed for use with 370V Capacitors




Figure A




Figure B

5.0" Diameter, 5/16" Diameter Shaft

HP	RPM	Voltage	Catalog Number	Bearings	Cap. MFD	Amps	Shaft N	Shell XI	Total C	Shaft Dia.	Mount	Ship Wt.
1/20	1500	230	1775P	SAB	3.0	.5	3.1	3.8	6.9	5/16"	Hub Ring	7
1/15	1500	230	1779P	SAB	3.0	.62	3.1	3.8	6.9	5/16"	Hub Ring	8

5.6" Permanent Split Capacitor

HP	RPM	Voltage	Catalog Number	Bearings	Cap. MFD	Amps	Shaft N	Shell XI	Total C	Mount	Ship Wt.
1/6	1550	208-230	6128	SAB	5.0	9.0	2.5	4.1	7.6	Resilient	17
	1550	208-230	1645	Ball	3.0	1.4	2.1	3.8	6.4	Stud	12
	1550/1	460	1265	SAB	3	0.55	3.1	4.1	7.1	Bracket	9
1/5	1075	208-230	1648	Ball	4.0	2.0	2.5	4.3	7.9	Stud	13
	1075	575	1093	Ball	4.0	.80	2.5	4.8	8.4	Stud	13
1/4	1550	230	6124	SAB	5.0	2.1	3.0	4.1	7.1	Band	13
	1625	208-230	6129	SAB	5.0	1.5	2.3	4.3	7.9	Resilient	17
	1625	230	3042	Ball	4.0	1.4	1.5	5.1	7.7	Hub Ring	12
	1625	230	8330	SAB	4.0	1.9	2.2	4.3	7.7	3 Lugs	12
	1625	380-420/460	8331	SAB	4.0	.95	2.2	4.3	7.7	3 Lugs	12
	1625	575	1312	SAB	-	0.7	3.1	4.8	7.9	Band	13
1/3	1625	208-230	6127	SAB	4.0	2.2	1.75	5.8	8.7	Resilient	17
	1625	208-230	7232	SAB	6.0	2.9	3.7	4.6	9.3	Hub Ring	16
	1075/2	208-230	1354	Ball	-	2.0	3.1	4.8	8.4	3 Lugs	11
1/2	1725	208-230	644	Ball	5.0	2.7	3.5	5.1	9.1	Stud	15
	1100/1	208-230/460	4941	BALL	12.5	2.8/1.5	4.5	6.9	11.4	Resilient	16