# Three Phase Series
# Commercial Condenser Fan Open Drip-Proof, Air Over

## APPLICATIONS:

Designed to meet manufacturer's requirements for condenser cooling fans in commercial air conditioning applications where 3 phase power id required.

## ADDITIONAL FEATURES to MOJAVE® Series:

- 158°F (70°C) Ambient Desigr

### Belly Band Mount, Flat and Keyway on Shaft

| HP | RPM/Spds | Voltage | Catalog Number | NEMA Frame | Amps | Shaft N | Shell Xl | Total C | Shaft Dia. | Ship Wt. |
|---|---|---|---|---|---|---|---|---|---|---|
| 3/4 | 1140 | 208-230/460 | 1817H | 56Z | 2.8/1.4 | 6.0 | 9.3 | 15.3 | 0.625 | 31.5 |
| 1 | 850 | 208-230/460 | 1828H | 56Z | 4.8/2.4 | 6.0 | .625 | 16.8 | 0.625 | 40 |
| | 850 | 575 | 1829H | 56Z | 1.7 | 6.0 | 10.8 | 16.8 | 0.625 | 41 |
| | 1140 | 208-230/460 | 1818H | 56Z | 4.2/2.1 | 6.0 | .625 | 14.8 | 0.625 | 27.3 |
| 1 1/2 | 850 | 208-230/460 | 1832H | 56Z | 6.8/3.3 | 6.0 | 10.8 | 16.8 | 0.625 | 44.1 |
| | 1140 | 208-230/460 | 1819H | 56Z | 5.4/2.7 | 6.0 | .625 | 15.8 | 0.625 | 35 |
| 2 | 1140 | 208-230/460 | 8987H | 56Z | 7.6/3.7 | 6.0 | 10.8 | 16.8 | 0.625 | 45 |

### Rigid Base Mount, Flat and Keyway on Shaft

| HP | RPM/ Spds | Voltage | Catalog Number | NEMA Frame | Amps | Shaft N | Shell Xl | Total C | Shaft Dia. | Ship Wt. |
|---|---|---|---|---|---|---|---|---|---|---|
| 3/4 | 1140 | 208-230/460 | 1826H | 56Z | 2.8/1.4 | 6.0 | 9.3 | 15.3 | 0.625 | 31.5 |
| 1 | 850 | 208-230/460 | 1833H | 56Z | 4.8/2.4 | 6.0 | 10.8 | 16.8 | 0.625 | 31.5 |
| | 1140 | 208-230/460 | 1820H | 56Z | 4.2/2.1 | 6.0 | .625 | 14.8 | 0.625 | 27 |
| 1 1/2 | 850 | 208-230/460 | 1831H | 56Z | 6.8/3.3 | 6.0 | 10.8 | 16.8 | 0.625 | 44.1 |
| | 1140 | 208-230/460 | 1821H | 56Z | 5.4/2.7 | 6.0 | .625 | 15.8 | 0.625 | 35 |
| 2 | 1140 | 208-230/460 | 1822H | 56Z | 7.6-7.4/3.7 | 6.0 | .625 | 16.8 | 0.625 | 45 |