
Permanent Split Capacitor Direct Drive Fan and Blower
5.6" Diameter Open Air Over

APPLICATIONS:

Residential and commercial direct drive fans and blowers.

FEATURES:

- Stud Extensions On Popular Models
- Suitable for Use With 370V Capacitors
- Class B Insulation
- 24" Leads
- Continuous Duty, Air Over
- SAB Bearings Have All Angle Thrust System
- Reversible Rotation
- For Flex Mount, Order Catalog #44; See Page 188-189
- Automatic Reset Thermal Overload Protector
- Connection and Capacitor Information Furnished In Nameplate Data
- 2.5" Diameter Hub Rings Included
- **Discount Symbol: DS-3HAC**



Hub Ring Mount (2.5") Except As Noted, Without Capacitor

HP	RPM/ Spds.	Voltage	Catalog Number	List	Cap. MFD	Amps	Shaft N	Base XD	Shell Xl	Total C	Ship Wt. (lbs)
1/4	1075/3	115	1863	$112	7.5	3.5	5.0	4.9	4.3	10.4	12
	1625/3	115	1690	$214	10.0	2.7	6.0	4.7	4.3	10.4	13
	1075/3	208-230	1971	$114	7.5	1.5	5.0	4.9	4.3	10.4	11
	1075/3	277	600	$236	4.0	2.0	5.0	5.1	4.6	10.7	14
1/3	1075/3	115	1864	$115	7.5	5.0	5.0	5.1	4.6	10.7	12
	1625/3	115	1692	$220	15.0	3.7	5.0	5.1	4.6	10.7	13
	1075/3	208-230	1972	$118	7.5	1.9	5.0	4.9	4.6	10.7	13
	1075/3	277	601	$218	4.0	2.2	5.0	5.2	4.3	10.7	14
	1625/3	208-230	1693	$150	5.0	2.1	5.0	5.1	4.7	10.4	13
1/3 / 1/9	825/2	208-230	5469	$218	7.5	2.4	4.5	--	5.3	9.8	17
1/2	825/2	208-230	8064	$249	20.0	4.4	2.5	5.6	6.1	9.0	21
	1075/3	115	1865	$139	10.0	6.5	4.0	6.0	5.4	10.4	19
	1625/3	115	1694	$235	15.0	5.5	5.0	5.9	5.3	11.4	17
	1075/3	208-230	1973	$144	10.0	2.9	5.0	5.9	5.3	11.4	19
	1075/3	277	602	$299	6.0	3.4	5.0	5.5	4.9	10.9	16
	1625/3	208-230	1695	$240	7.5	3.1-3.0	5.0	5.9	5.3	11.4	17
1/2 - 1/6	1075/2	115	5460	$148	12.5/7	7.3	5.0	5.4	4.8	9.8	15
	1075/2	208-230	5461	$151	10/5	3.6	5.0	5.4	4.8	9.8	15
3/4	1625/3	115	1696	$250	15.0	8.6	5.0	6.1	5.6	11.7	20
	1625/3	208-230	1697	$255	10.0	4.4-4.2	5.0	6.1	5.6	11.7	18
	1075/3	115	8904	$159	15.0	9.5	4.0	6.0	5.4	10.4	19
	1075/3	208-230	8905	$160	15.0	4.0	4.0	6.0	5.4	10.4	19
	1075/3	277	5847	$298	15.0	4.1	4.9	6.7	5.6	13.2	19
	1075/4	115	3340	$340	7.5	12.1	6.0	4.8	5.3	12.4	18
3/4 - 1/5	1075/2	115	5470	$177	20/10	8.1	5.0	6.6	6.1	11.6	22
	1075/2	208-230	5471	$181	20/10	4.1	5.0	6.6	6.1	11.6	21
1	1075/4	115	6452	$221	15.0	11.2	5.0	--	5.8	10.8	18
	1075/3	115	8906	$298	20.0	12.1	5.0	6.6	6.1	12.2	20
	1075/3	208-230	8907	$301	20.0	5.6	5.0	6.6	6.1	12.2	21
	1625/3	115	1699	$265	25.0	11.1	6.0	6.4	5.9	12.9	21